



Professional

3000



**KS GROUP**  
STEAM CLEANERS DIVISION



# 3000 LINE



## 3000

## 3000D

## 3000ID

**Description** Steam cleaner with continuous flow, vacuum (wet and dry) with water filter Steam cleaner with continuous flow, vacuum (wet and dry) with water filter plus the option of the detergent injection function Steam cleaner with continuous flow, vacuum (wet and dry) with water filter plus the option of the hot water rinsing function

	grey	blue	silver
Colour	grey	blue	silver
Detergent Tank capacity	--	1,5 l	--
Detergent tank - level alarm	--	visual and acoustic	--
Detergent injection quantity	--	from 3 to 10 cc/min (different regulation)	--
Water injection quantity:			
- 100V	--	--	from 6,0 to 7,0 cc/min (different EV regulation)
- 120V	--	--	from 8,5 to 9,5 cc/min (different EV regulation)
- 230V	--	--	from 14 to 15 cc/min (different EV regulation)
Pressure (bar) (100V-120V-230V)	5 - 6,5 - 6,5	5 - 6,5 - 6,5	5 - 6,5 - 6,5
Voltage (100V-120V-230V)	60Hz - 60Hz - 50Hz	60Hz - 60Hz - 50Hz	60Hz - 60Hz - 50Hz
Total Power Consumption (W) (100V-120V-230V)	2350 - 2750 - 3200/3400	2350 - 2750 - 3200/3400	2350 - 2750 - 4200/4400
Boiler Power Consumption (W) (100V-120V-230V)	1350 - 1750 - 2200	1350 - 1750 - 2200	1350 - 1750 - 3200
Iron Power Consumption (W) (100V-120V-230V)	--	--	--
Vac Motor Power Consumption (W) (100V-120V-230V)	1000 - 1000 - 1200/1000	1000 - 1000 - 1200/1000	1000 - 1000 - 1200/1000
Boiler material	Stainless Steel AISI 304	Stainless Steel AISI 304	Stainless Steel AISI 304
Boiler volume (l)	2,6	2,6	2,6
Tank capacity (l)	2,2	2,2	2,2
Min. Waste Tank level	0,3	0,3	0,3
Waste tank capacity (l)	1,8	1,8	1,8
Vac Motor suction power (Kpa) (100V-120V-230V)	17 - 18 - 18/19	17 - 18 - 18/19	17 - 18 - 18/19
Steam production	continuous flow	continuous flow	continuous flow
Boiler Steam temperature (100V-120V-230V)	151°C - 161°C - 161°C	151°C - 161°C - 161°C	151°C - 161°C - 161°C
Water pump power (100V-120V-230V)	41W - 41W - 48W	41W - 41W - 48W	41W - 41W - 48W
Water level alarm	visual and acoustic	visual and acoustic	visual and acoustic
Pressure alarm	visual	visual	visual
Low tension voltage on handgrip	9 V	9 V	9 V
Heating time (minutes) (100V-120V-230V)	10 - 6 - 5	10 - 6 - 5	10 - 6 - 5
Power cable (100V-120V-230V)	4 m - 5 m - 7 m	4 m - 5 m - 7 m	4 m - 5 m - 7 m
Steam regulation on steam hose	yes	yes	yes
Dimensions (LxWxH)	530mm X 400mm X H.400mm	530mm X 400mm X H.400mm	530mm X 400mm X H.400mm
Net weight (kg)	14 Kg	14,50 Kg	14,50 Kg
Certification Reached	CE	CE	CE
Certification on work	GS-Nemko+IPX4	GS-Nemko+IPX4	GS-Nemko+IPX4
Warranty (year) (100V-120V-230V)	1 - 1 - 2	1 - 1 - 2	1 - 1 - 2



Steam and vac plus the option of mild detergent injection or hot water rinsing function. Comes with a great range of attachments to cover most applications, and has a powerful 6.5 bar steam pressure. Using steam is an effective and environmentally friendly method of cleaning hard surfaces. The applications for this machine are many and it is ideal in hotels, guest houses, hospitals, childcare, gyms, sports clubs, commercial kitchens, bathrooms, public areas, bedding and furnishings, floors, walls and ceilings etc. This steamer is light and versatile, easily used by all staff also thanks to its easy to handle trolley.



Via Trieste, 5 - I-25030 Castelvati (Bs) Italy  
Tel. +39 030 7080550 - Fax +39 030 718104  
[www.ksgsteamdivision.com](http://www.ksgsteamdivision.com)    [info.steamdept@ksgroup.it](mailto:info.steamdept@ksgroup.it)



# Standard ACCESSORIES



- 17 - 2,45 m steam hose
- 22 - Bottle
- 29 - Extension pipes
- 31 - 30 cm large brush
- 31A - 30 cm bristled frame
- 31B - 30 cm rubber frame
- 31C - 30 cm stiff frame
- 32 - 15 cm small brush
- 32A - 15 cm bristled frame
- 32B - 15 cm rubber frame
- 32C - 25 cm rubber frame
- 33 - Sponge covering for small brush
- 34 - Universal mouth
- 34A - Vertical mouth
- 34B - Horizontal mouth
- 34C - Ferrule with fixed extension
- 34D - 30 mm small brush with polyester bristles
- 34E - 30 mm small brush with steel bristles
- 34F - 60 mm brush with polyester bristles
- 34G - Spatula
- 35 - Spanner for boiler draining

# Optional ACCESSORIES



- 5 - Very soft bristle brush
- 7 - Sponge covering for large brush
- 8 - Extension pipe steam only
- 11 - Plunger
- 12 - 60 mm brush with red polyester bristles
- 14 - 38 mm small brush with polyester bristles
- 15 - 38 mm small brush with steel bristles
- 16 - 38 mm small brush with brass bristles
- 24 - Armchair beater
- 26 - 24 cm transparent mouth
- 37 - Rectangular brush with soft bristles
- 41 - Rectangular brush with polyester bristles
- 42 - Rectangular brush with steel bristles
- 43 - Rectangular brush with brass bristles
- 48 - 25 cm extension hose steam only
- 49 - 5 m steam hose
- 50 - Trolley
- 52 - Steam hose only steam
- 53 - 25 cm wall mop
- 54 - 10lt Tank Detergent (for Mod.3000D)
- 55 - 39 cm floor mop
- 56 - Short transparent mouth
- 57 - Long transparent mouth
- 58 - Microfiber cloth floor mop
- 59 - Microfiber cloth wall mop
- 60 - Floor mop kit
- 61 - Wall mop kit
- 62 - Trolley with or without tank system (new design)