





TECHNICAL DATA SHEET

NAME	REFERENCE
OPTICAL SENSOR OPERATED HAND DRYER "IBERO" BRIGHT STAINLESS STEEL	AA92000
DESCRIPTION	
HIGH QUALITY AND PERFORMANCE TRADITIONAL HAND DRYER DOUBLE ELECTRICAL INSULATION OPTICAL SENSOR OPERATED : AUTOMATIC START AND STOP CLASS II: NO GROUNDING WIRE REQUIRED, AT 0,6 mts FROM WATER POINT HIGH QUALITY BRIGHT STAINLESS STEEL	
ELECTRICAL SCHEME	
 <p>1. THERMAL FUSE 2. THERMAL CUT-OFF (IN HEATING ELEMENT) 3. HEATING ELEMENT POWER 1800 W 230 V - 50 HZ 4. THERMAL CUT-OFF (IN MOTOR) 5. MOTOR 230 V - 50 HZ 6. ELECTRONIC CIRCUIT 7. OPTICAL SENSOR</p>	EAN CODE 8427950323102

CHARACTERISTICS				
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 220	WIDTH: 280	DEPTH: 210
	WEIGHT (Kg)	3,625		
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 285	WIDTH: 345	DEPTH: 295
	WEIGHT (Kg)	4,320		
MATERIALS	BRIGHT STAINLESS STEEL COVER AISI 304 INTERNAL COMPONENTS IN ABS AND POLYCARBONATE"V0" NOZZLE IN CHROME ABS			
COLOUR / FINISH	BRIGHT STAINLESS STEEL COVER CHROME NOZZLE			
ELECTRICAL FEATURES	VOLTAGE: 230V. AC FREQUENCY: 50 Hz. CONSUMPTION: 8,8 Amp. MOTOR POWER: 200 W. HEATING ELEMENT POWER: 1800 W. TOTAL POWER: 2000 W. MOTOR RPM: 4250 TYPE OF MOTOR : BRUSHED		AIRSPEED: 121 Km/HOUR EFFECTIVE AIRFLOW: 300 m ³ /HOUR SOUND PRESSURE: 77,5 Db. AIR TEMPERATURE: 54,1 °C (At a distance of 10 cm.) ELECTRICAL INSULATION: CLASS II CERTIFICATIONS: TÜV, GS, UL AND CE PROTECTION RATIO: IP23	
	FIXING	BY MEANS OF FOUR SCREWS AND FOUR WALL PLUGS - PROVIDED		
PACKAGING	SINGLE UNIT PACKAGING		Approved by: Quality Control Dept	
			DATE: 12/05/2015	