



(OPTIONAL)

**Intrinsically Safe Flashlight
For Use In Hazardous Locations**

DF104-2W



IECEX





REACH



RoHS

TECHNOLOGY



Fastener



Valve



Two Ways Position Clip



Color

SPECS

| | Low | High |
|---------------|---------------|-------------|
| Battery Size | 3*C | |
| Light Source | Cree XP-E LED | |
| Mode | High/Low/Off | |
| Light Output | 55lm | 124lm |
| Beam Distance | 120m | 185m |
| Run Time | 80hrs | 42hrs 30min |
| IP Rating | IP67 | |
| Weight | 190g | |
| Dimension | 225*60*85mm | |

Certifications & Standards:

| | | |
|---------|--|----------|
| - UL | CLASS I DIV I GRP ABCD CLASS II DIV I GRP EFG CLASS III TEMP CODE: T4 | DF104-2W |
| - ATEX | Ex II 1 G Ex ia IIC T4 | |
| - IECEX | Ex ia IIC T4 Ga | |
| - CE | Approved | |
| - ROHS | Approved | |
| - REACH | Approved | |

- USES CREE XP-E LED
- CLIP ON FUNCTIONS
- TWO WAYS POSITION CLIP
- HIGH / LOW / OFF
- FASTENER PREVENTS FROM OPENING TORCH IN HAZARDOUS PLACES.
- VALVE DESIGN HELPS TO HYDRO GEN GAS RELEASED.

